

Jednofazowe silniki indukcyjne z kondensatorem pracy, w obudowach aluminiowych. IP 55

W Wymiary montażowe i gabarytowe

W.m.	Wymiary montażowe																			Wymiary gabarytowe						
	B3									B5						B14				AA	AC	AD	HD	L		
	A	B	C	D	E	F	G	H	K	M	N	P	R	S	T	M	N	P	R						S	T
56	90	71	36	9	20	3	7,2	56	5,8	98	80	120	0	7	3,0	65	50	80	0	M5	2,5	108	115	156	100	192
63	100	80	40	11	23	4	8,5	63	7	115	95	140	0	10	3,0	75	60	90	0	M5	2,5	120	130	179	116	212
71	112	90	45	14	30	5	11	71	7	130	110	160	0	10	3,5	85	70	105	0	M6	2,5	132	145	194	123	240
80	125	100	50	19	40	6	15,5	80	10	165	130	200	0	12	3,5	100	80	120	0	M6	3,0	157	165	223	143	290
90S	140	100	56	24	50	8	20	90	10	165	130	200	0	12	3,5	115	95	140	0	M8	3,0	172	185	240	150	310
90L	140	125	56	24	50	8	20	90	10	165	130	200	0	12	3,5	115	95	140	0	M8	3,0	172	185	240	150	335
100L	160	140	63	28	60	8	24	100	12	215	180	250	0	15	4,0	130	110	160	0	M8	3,5	196	205	260	160	357

